



Multi-Axis Personnel Lift

LPC E SERIES



APPLICATIONS:

- Paint Spray Booths
- Hazardous Environments
- Preparation Areas
- Sanding Stations
- Wash Down Areas
- Replace Ladders/Scaffolds



1-715-839-8280
(F) 715-839-8647
www.lpi-inc.com
international@lpi-inc.com

LPCE SERIES

ERGONOMIC LIFTING SYSTEMS... PRODUCTIVE SOLUTIONS.

SPECIFICATIONS

Model Number	Raised Platform Height	Minimum Booth Height	Distance to front of platform fully retracted	Distance to front of platform fully extended
LPCEP-2025	6' 5"	13' 1"	3' 3"	8' 1"
LPCEP-2525	8' 2"	14' 9"	3' 3"	8' 1"
LPCEP-3025	9' 10"	16' 5"	3' 3"	8' 1"
LPCEP-3525	11' 6"	18' 0"	3' 3"	8' 1"
LPCEP-4025	13' 1"	19' 8"	3' 3"	8' 1"
LPCEP-4525	14' 9"	21' 4"	3' 3"	8' 1"
LPCEP-5025	16' 5"	23' 0"	3' 3"	8' 1"
LPCEP-5525	18' 0"	24' 7"	3' 3"	8' 1"

Model Number	Raised Platform Height	Minimum Booth Height	Distance to front of platform fully retracted	Distance to front of platform fully extended
LPCEP-2025	2,0 m	4,0 m	1 m	2464 mm
LPCEP-2525	2,5 m	4,5 m	1 m	2464 mm
LPCEP-3025	3,0 m	5,0 m	1 m	2464 mm
LPCEP-3525	3,5 m	5,5 m	1 m	2464 mm
LPCEP-4025	4,0 m	6,0 m	1 m	2464 mm
LPCEP-4525	4,5 m	6,5 m	1 m	2464 mm
LPCEP-5025	5,0 m	7,0 m	1 m	2464 mm
LPCEP-5525	5,5 m	7,5 m	1 m	2464 mm

FEATURES

- Multi-Axis Lift movement, X, Y & Z
- X-Axis (lengthwise travel) is rail guided and variable speed
- Y-Axis (In/Out) travels 1.5 meters from retracted to extended positions
- Z-Axis (Up/Down) available in elevations up to 5.5 meters
- Y & Z axes are screw driven providing smooth and stable movement
- Operator controls in the platform and on the base of the lift
- Base controls have keyed lock-out to prevent unauthorized use
- Powered by air makes it suitable for use in paint booths
- Platform maximum rated capacity: 202 Kg (two people and equipment)
- For auxiliary tools, platform has an unooled air supply connection

OPTIONS

- Auxiliary Flex Track: plastic flex chain track that attaches to the mast and runs out to the operator platform to contain auxiliary lines and prevent them from tangling
- Contact Bumper: padded bumper that shuts down all movement of lift if contact is made with product, from any direction
- Paint Pressure Pot Carrier: attaches to base of lift to move pressure pot with you as you work



A. Optional Auxiliary Flex Track



B. Optional Contact Bumper



C. Optional Paint Pot Carrier

LPI® promotes a safe and ergonomic work environment which increases worker productivity.
Specifications may be changed subsequent to printing.
No part of this information may be reproduced in whole or part without written permission.